HALOFOG SYSTEM · COMPRESSED AIR

Halofog 300

A compact Halofog system with 5–10 µm droplets. Its capacity is smaller than Synofog's, but it is easy to automate: small regular treatments with less product used at a time. Runs off a compressor.







OUTPUT
about 2–2.5 L/h per nozzle

DROPLET SIZE
5–10 µm, guaranteed < 9 µm (measurement certificate...

DRIVE AND SUPPLY
3.3–3.5 bar compressed air, 150 L/min per nozzle, from...

PRICE
on request

We will quote the price and delivery time for your configuration. Message us on WhatsApp and we will reply the same day.

Specifications · Halofog 300

Type	Halofog system
Output	about 2–2.5 L/h per nozzle
Droplet size	5–10 µm, guaranteed < 9 µm (measurement certificate available)
Drive and supply	3.3–3.5 bar compressed air, 150 L/min per nozzle, from your own compressor
Solution tank	none: lifts liquid up to 60 cm, no pump
Control	manual or automatic; connects to the store computer
Mobility	portable unit or fixed system with several nozzles

Features

- Dry fog: surfaces stay dry
- For small stores (up to ~300 t)
- Continuous or intermittent operation
- Chemical-resistant hoses, stainless-steel parts

Delivery and service in Kazakhstan

Delivery and customs clearance
We deliver the equipment to your site and handle customs ourselves.

Commissioning and training
We commission the equipment on site and train your operators in Russian or Kazakh.

Payment in tenge and paperwork
A contract with a Kazakh company, payment in tenge and a full set of accounting documents.

Warranty, service and spare parts
Warranty and seasonal maintenance, spare parts and consumables close at hand, in Kazakhstan.

Yermek Zhunussov
Director · Will choose the equipment for your store and answer your questions

+7 700 300 2222 · WhatsApp
+7 777 247 10 90 · WhatsApp
info@tarakan.kz · Almaty

Specifications may change; please confirm when ordering. Trademarks belong to their respective owners. Prepared 22.11.2026.